



DAESAN portable, light weight hand chain hoists are compact and provide a dependable working tool for industrial maintenance, construction sites, machine shops, and production situations where parts need to be positioned accurately but infrequently.

Covers: Protective steel covers can easily be removed for inspection and maintenance. Wheel cover & brake cover protect block from dust and rain

Mechnical Load Brake: Can hold a capacity load stationary at any position.

Hooks: All hooks are drop forged, heat treated steel with spring type latches. Both hook rotates 360 for easy rigging.

Chain Guide: Allows smooth operation of load chain.

Load Sheaves: Deep cast pockets precisely fit the load chain. Load shafts are supported by prelubricated bearings for smooth operation.

Load Chain: Electric welded G80 alloy steel chain is heat treated for wear resistance and strength. Accurately and uniformly sized to seat properly in load sheaves.

CHAIN BLOCK



ISN TYPE

MODEL NO		DSN0.5	DSN1	DSN1.5	DSN 2NEW	DSN2	DSN3	DSN5	DSN10	DSN15	DSN20
Capacity(SWL)	ton	0.5t	1t	1.5t	2t	2t	3t	5t	10t	15t	20t
Chainfall	no.	1	1	1	2	1	2	2	4	6	8
Standard Lift	meter	2.5	2.5	2.5	3	3	3	3	3.5	3.5	3.5
Load chain dia.	mm	6.3x19.1	6.3x19.1	7.1x21.0	6.3x19.1	7.9x23.0	7.1x21.0	9.0x27.0	9.0x27.0	9.0x27.0	9.0x27.0
Hand chain	mm	5.0x22.8									
Net welght	kg	11	12	14	18	22	23	41	95	150	200
Pulling efforts	kg	24	33	34	33	34	35	39	41	41x2	41x2
Dimension	а	147	147	147	150	184	147	185	185	212	212
4	b	145	145	164	179	187	206	258	367	745	873
	C	310	330	360	430	380	480	620	820	850	970

DSN Series

